## **Amendments to the Claims**

- 1. (Original) A process for producing a transparent multilayer stretched product, comprising: providing a resin laminate including at least one layer of polyglycolic acid resin, heat-forming and cooling the resin laminate, reheating the laminate until the polyglycolic acid resin layer is crystallized to be opaque, and then stretching the reheated resin laminate.
- 2. (Original) A process according to Claim 1, wherein the resin laminate after the cooling is transparent.
- 3. (Currently amended) A process according to Claim 1-or 2, wherein the polyglycolic acid resin occupies at most 10 wt.% of the resin laminate.
- 4. (Currently amended) A process according to any one of Claims 1 3 Claim 1, wherein the polyglycolic acid resin layer comprises a polyglycolic acid resin having a sufficiently high content of polymerized glycolic acid units as to exhibit a gas-barrier property.
- 5. (Original) A process according to Claim 4, wherein the polyglycolic acid resin comprises glycolic acid homopolymer.
- 6. (Currently amended) A process according to any one of Claims 1-5 Claim 1, wherein the resin laminate immediately prior to the stretching exhibits a haze of at least 40%.
- 7. (Currently amended) A process according to any one of Claim 1 6 Claim 1, wherein the resin laminate includes an aromatic polyester resin layer in addition to the polyglycolic acid resin layer.

- 8. (Currently amended) A process according to any one of Claims 1 6 Claim 1, wherein the resin laminate includes another biodegradable resin layer in addition to the polyglycolic acid resin layer.
- 9. (Currently amended) A multilayer stretched product obtainable through a process a production process according to any one of Claims 1 8 Claim 1.